FLEXTAPE®



TEMPERATURE MAINTENANCE SYSTEMS

Anti-condensation tapes for electric motors

www.flexelec.com

RSV







Characteristics



- · Maximum heat transfer.
- · Damp-proof.
- Extended range of lengths and power ratings.
- Power cable: length 500 mm as standard.
- Voltage 230 V as standard (115 V on request).
- Approved for use in motors runnning in explosive atmospheres.
- ATEX certificate: Sira N° 02ATEX3410U.
- IECEx certificate: SIR 10.0151U


Applications

RSV heating tapes are specially designed for electric motors to prevent condensation.

These elements are ready to be incorporated into the motor coil with their fibre glass braid.

RSV tapes are practical to use and very efficient. They transfer a maximum amount of heat as they are in direct contact with the stator. RSV tapes are generally energised when the motor stops.

To ensure that these heating elements enjoy a long service life, we recommend using a control device.



silicon elastomer insulation Heating wire

Fibre glass core

Fibre glass braid

Standard models

Heating tapes

Length (m)	Power (W)
0.30	25
0.43	25
0.68	40
0.79	26
1.01	42
1.06	50
1.47	65
1.70	75
1.70	100
1.85	100

Fibre glass sheath

Use

Heating tapes are series resistors. Consult the pages of the catalogue devoted to the corresponding general operating principles, general instructions for use and accessories.

Heating wire Nickel-Copper or Nickel-Chrome Heating element insulation Silicon elastomer External insulation Fibre glass braid Dimensions 3 x 11 mm Permissible surface from - 70°C to + 200°C temperature Tolerances Power: ± 10 % Connection

FLEXELEC S.A.S

10, rue des frères Lumière Z.A. du Bois Rond 69720 ST BONNET DE MURE - FRANCE Tel: +33 (0)4.72.48.30.90 Fax: +33 (0)4.78.40.82.81

FLEXELEC Dept

OMERIN ASIA Pte Ltd 51 Goldhill Plaza #08-12/01 SINGAPORE 308900 Tel: + 65.6255.4778 Fax: + 65.6255.4779 F-mail: sales@omerin.com.sq.

FLEXELEC (UK) Ltd

Unit 11 Kings Park Industrial Estate Primrose Hill - KINGS LANGLEY Hertfordshire - WD4 8ST - UK Tel: + 44 (0) 1923.274477 Fax: + 44 (0) 1923.270264

and end insulation

FLEXELEC Dept

Fibre glass sheath

OMERIN GmbH Buchwiese 16 D-65510 IDSTEIN - GERMANY Tel: + 49 (0) 6126.94.31-0 Fax: + 49 (0) 6126.83.99